

IN THE CLAIMS:

Please substitute amended claims 1, 3, 4, 7-9, 13-16, 19-23 and 27-29, as follows:

1. (Amended) An electromagnetic drive for controlling an amount of light of a luminous flux, said electromagnetic drive comprising:

5 a solenoid having a coil whose winding axis is disposed in parallel with a direction of the luminous flux;

a movable plunger that is movable in parallel with the direction of the luminous flux by a magnetic force of the solenoid; and

10 a blade member driven by the movable plunger for controlling the amount of light of the luminous flux.

3. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 1, wherein the movable plunger includes a band of projection provided around the movable plunger in a vicinity of an end portion of the movable plunger, and wherein the movable plunger is moved in the solenoid using the band of projection.

4. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 1, further comprising:

a bearing portion for supporting the movable plunger at an end portion thereof exposed out of the solenoid.

7. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 6, further comprising is a bearing portion which supports the movable plunger at an end portion thereof exposed out of the solenoid,
5 and a band of projection formed on a peripheral surface in a vicinity of the end portion of the movable plunger to be fitted into the bearing portion, wherein the movable plunger is slidably movable in the bearing portion using the projection.

8. (Amended) An electromagnetic drive for controlling an amount of light of a luminous flux, said electromagnetic drive comprising:

a solenoid having a coil whose winding axis is disposed in
5 parallel with a direction of the luminous flux;

a movable plunger that is movable in a direction parallel to the direction of the luminous flux by a magnetic force of the solenoid;

a switching member for switching a direction in which a
10 locomotive faculty of the movable plunger acts from the direction parallel to the direction of the luminous flux to a direction perpendicular to the direction of the luminous flux; and

a blade member driven by the locomotive faculty obtained by the switching member.

9. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 8, wherein the switching member pivots about the winding axis in parallel with the direction of the luminous flux.

13. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 3, wherein the movable plunger includes a band of projection provided around the movable plunger in a vicinity of an end portion of the movable plunger, and wherein the movable plunger is movable in the solenoid using the band of projection.

14. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 10, further comprising:

a bearing portion for supporting the movable plunger at an end portion thereof exposed out of the solenoid.

15. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 14, wherein the movable plunger includes a band of projection formed on a peripheral surface in a vicinity of the end portion of the movable plunger to be fitted into the bearing portion, and wherein the movable plunger is movable in the bearing portion using the band of projection.

16. (Amended) An electromagnetic drive for controlling an amount of light of a luminous flux, said electromagnetic drive comprising:

a plurality of solenoids having coils whose winding axes lie perpendicular to a direction of the luminous flux;

a movable plunger that is movable along one of the winding axes by a magnetic force of the solenoid; and

a blade member driven by the movable plunger for controlling the amount of light of the luminous flux.

19. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 16, wherein the plurality of solenoids are disposed along the direction of the luminous flux in such a manner that the winding axes of the coils are respectively lying on planes perpendicular to the direction of the luminous flux, in parallel with each other.

20. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 16, wherein the movable plunger includes a band of projection provided around the movable plunger in a vicinity of an end portion of the movable plunger, and wherein the movable plunger is movable in the solenoid using the band of projection.

21. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 19, further comprising:

5 a bearing portion for supporting the movable plunger at an end portion thereof exposed out of the solenoid.

22. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 21, wherein the movable plunger includes a band of projection formed on a peripheral surface in a vicinity of the end portion of the movable plunger to be fitted into the bearing portion, and wherein the movable plunger is movable in the bearing portion using the band of projection.

23. (Amended) An electromagnetic drive for controlling an amount of light of a luminous flux comprising:

a plurality of solenoids having respective center axes corresponding to respective different lines;

5 a movable plunger that is movable along one of the center axes of the plurality of solenoids by a magnetic force of the plurality of solenoids; and

a yoke member for forming magnetic fluxes generated from the plurality of solenoids into a loop.

24. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 23, wherein

the movable plunger includes a projection provided around the movable plunger in a vicinity of an end portion of the movable plunger, and wherein the movable plunger is moved in the solenoid using the projection.

28. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 26, further comprising:

15
25
60
a bearing portion for supporting the movable plunger at an end portion thereof exposed out of the solenoid.

29. (Amended) An electromagnetic drive for controlling the amount of light of a luminous flux according to Claim 28, wherein the movable plunger includes a band of projection formed on a peripheral surface in a vicinity of the end portion of the movable plunger to be fitted into the bearing portion, and wherein the movable plunger is movable in the bearing portion using the band of projection.